 Copyright © 2024 Hallbrookcomponents.com

TRANSPAK TP-702CQ3-T

Tandem High-Speed Corrugated Strapper with Integrated Squaring System





Description:

The TRANSPAK TP-702CQ3-T is an all-electric tandem corrugated strapper featuring an integrated 3-side squaring system. It delivers efficient and precise bundling, processing up to 32 bundles per minute, making it ideal for high-capacity Flexo Folder Gluers and Casemakers in demanding production environments. With advanced features like motorized full-width press and Siemens PLC with HMI, this machine ensures reliable, intuitive operation tailored for high-volume industries.

Features:

1. **Integrated 3-Side Squaring System:** Ensures precise bundle positioning and handling.
2. **Siemens PLC with HMI:** Provides user-friendly operation and enhanced control.
3. **Compact and Robust Strapping Head:** Designed for multiple operation modes and high performance.
4. **Motorized Full-Width Press:** Guarantees secure and consistent bundling.
5. **Free Access to Strap Guides:** Patent-registered design allows easy maintenance and adjustment.

Key Product Benefits:

1. **High-Speed Bundling:** Processes up to 32 bundles per minute, reducing production time.
2. **Versatile Applications:** Compatible with Flexo Folder Gluers and Casemakers, ensuring seamless integration.
3. **Efficient Workflow:** Motorized press and automation features optimize packaging operations.

Applications:

The TRANSPAK TP-702CQ3-T Tandem Strapper is ideal for high-volume corrugated packaging applications, including:

- Bundling for Flexo Folder Gluers and Casemakers.
- Efficient strapping for industrial corrugated board manufacturing.
- High-speed production lines requiring secure and precise packaging solutions.

Specifications	
Arch Size	1650 mm (W) x 450 mm (H)
Capacity	Up to 32 bundles/minute (single strap), 26 bundles/minute (double straps)
Strap Width	5 mm, 6 mm, or 9 mm
Tension Range	1 - 32 kg
Electrical Requirements	220V, 380V, 400V, 415V, 50/60Hz, 3 Phase
Item Number	41202180

For more details, pricing, and orders, please contact: support@sal-tech.com